

General

In-line four stroke diesel engine with direct injection. Rotation direction, anti-clockwise viewed towards flywheel.

Turbocharged

Number of cylinders			6
Displacement, total		litre in ³	16,12 983,9
Firing order			1-5-3-6-2-4
Bore		mm in	144 5,67
Stroke		mm in	165 6,50
Compression ratio			16.5:1
Wet weight	Engine only	kg	1550
		lb	3417
	Engine incl. cooling system and air filtration system	kg	1751
lb		3860	
	Engine incl. cooling system, air filtration system, and frame	kg	2020
		lb	4453

Performance

			rpm	1500	1800
Standby Power	without fan	kW		484	565
		hp		658	768
	with fan	kW			
See diagram for fan power consumption					
Prime Power	without fan	kW		441	513
		hp		600	698
	with fan	kW			
See diagram for fan power consumption					
Torque at:	Standby Power	Nm		3081	2997
		lbft		2272	2211
	Prime Power	Nm		2807	2722
		lbft		2071	2007
Mean piston speed		m/s		8,3	9,9
		ft/sec		27,1	32,6
Effective mean pressure at:	Standby Power	MPa		2,4	2,3
		psi		348	339
Effective mean pressure at:	Prime Power	MPa		2,2	2,1
		psi		317	308
Max combustion pressure at:	Standby Power	MPa		18,6	19,1
		psi		2698	2770
Max combustion pressure at:	Prime Power	MPa		16,7	18,4
		psi		2422	2669
Total mass moment of inertia, J (mR ²)		kgm ²		4,20	
		lbft ²		99,7	
Friction Power		kW		40	56
		hp		54,4	76,16
Derating see Technical Diagrams					

Engine noise emission

Test Standards: ISO 3744-1981 (E) sound power

 Tolerance ± 0.75 dB(A)

		rpm	1500	1800
Measured sound power Lw	No load	dB(A)	112,8	116,8
	Standby Power	dB(A)	114,6	118,2
	Prime Power	dB(A)	114,5	118,1
Calculated sound pressure Lp at 1 m	No load	dB(A)	101,8	105,8
	Standby Power	dB(A)	103,6	107,2
	Prime Power	dB(A)	103,5	107,1

Unsilenced exhaust noise

Fan ratio 1:1,13

Data calculated as sound pressure Lp.

Assumed microphone distance 1 m

	rpm	1500	1800
Standby Power	dB(A)	116	118
Prime Power	dB(A)	115	118

Test conditions for load acceptance data

Warm engine.	Generator	Model	Type of AVR
	Stamford	HCI534 D1	MX341
AVR Settings	UFRO : Std-setting 47Hz / 57Hz / 400 V		

Load acceptance performance can vary due to actual alternator inertia, voltage regulator, type of load and local ambient conditions. Please note that load step 0-100% is based on calculation.

Single step load performance at 1500 rpm

Load (%)	Speed diff (%)		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	1,4	1,6	0,7	0,8	20-100	18,1	21,4	3,4	4,8
0-40	3,0	3,0	1,0	1,1	40-100	5,5	6,1	1,5	2,7
0-55		7,0		2,2	55-100		5,5		2,4
0-60	7,0	8,7	2,1	1,8	60-100	3,1	5,5	1,1	2,3
0-65		10,0		2,6	65-100		5,3		2,3
0-72	10,0		2,5		72-100	2,7		1,3	
0-80	12,1	16,7	3,3	3,4	80-100	1,7	2,1	0,7	1,4
0-100*	19,2	28,5	5,0	4,7					
100-0	6,0	6,6	1,2	1,5					

Single step load performance at 1800 rpm

Load (%)	Speed diff %		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	1,1	1,1	0,4	0,5	20-100	8,7	9,5	1,6	1,7
0-40	2,4	2,1	0,6	0,8	40-100	4,3	4,1	1,6	1,6
0-60	3,8	4,5	1,0	1,4	60-100	2,4	2,2	1,3	3,0
0-70		7,0		1,2	70-100		1,6		0,9
0-77	7,0		1,3		77-100	1,2		0,6	
0-80	7,5	8,7	1,2	1,5	80-100	1,0	1,1	0,6	2,6
0-83		10,0		1,5	83-100		1,0		1,1
0-91	10,0		1,5		91-100	0,5		0,3	
0-100*	11,8	14,0	1,7	1,7					
100-0	4,1	4,1	0,8	0,7					

Cold start performance

			rpm	1500	1800
Time from start to stay within 0.5% of no load speed at ambient temperature:	°C	20	s	4,5	4,8
		5	s	5,2	5,0
		-15*	s	5,1	5,8
		-30**	s	7,4	6,5

* With manifold heater 4 kW engaged, lubrication oil 15W/40 and block heater.

** With manifold heater 4 kW engaged, lubrication oil 5W/30 and block heater, Fuel MK-1.

Block heater type	Make	Power kW	Engaged hours	Cooling water temp engine block
	Volvo	2	12	10°C 50°F

Lubrication system

			rpm	1500	1800
Lubricating oil consumption	Standby Power	litre/h		0,10	0,11
		US gal/h		0,026	0,029
	Prime Power	litre/h		0,10	0,12
		US gal/h		0,026	0,032
Oil system capacity including filters		litre		48	
		US gal		12,7	
Oil sump capacity:	max	litre		42	
		US gal		11,1	
	min	litre		32	
		US gal		8,5	
Oil change intervals/specifications:	VDS 3	h		600	
	VDS 2	h		400	
		h			
Engine angularity limits:	front up	°		30	
	front down	°		30	
	side tilt	°		30	
Oil pressure at rated speed		kPa		300 - 650	
		psi		44 - 94	
Lubrication oil temperature in oil sump:	max	°C		130	
		°F		266	
Oil filter micron size		µ		40,000	

* See also general section in the sales guide

Fuel system		rpm	1500	1800
Standby Power Specific fuel consumption at:	25%	g/kWh lb/hph	232 0,376	226 0,366
	50%	g/kWh lb/hph	211 0,342	201 0,326
	75%	g/kWh lb/hph	206 0,334	196 0,318
	100%	g/kWh lb/hph	200 0,324	204 0,331
Prime Power Specific fuel consumption at:	25%	g/kWh lb/hph	235 0,381	230 0,373
	50%	g/kWh lb/hph	212 0,344	203 0,329
	75%	g/kWh lb/hph	205 0,332	195 0,316
	100%	g/kWh lb/hph	198 0,321	200 0,324

Fuel system		rpm	1500	1800
Fuel to conform to	ASTM-D975-No1 and 2D JIS KK 2204, EN 590			
System supply flow at:	litre/h		141,0	164,0
	US gal/h		37,3	43,3
Fuel supply line max restriction (Measured at fuel inlet connection)	kPa		30,0	30,0
	psi		4,4	4,4
Fuel supply line max pressure, engine stopped	kPa		0,0	0,0
	psi			
System return flow	litre/h		25,0	25,0
	US gal/h		6,6	6,6
Fuel return line max restriction (Measured at fuel return connection)	kPa		20,0	20,0
	psi		2,9	2,9
Maximum allowable inlet fuel temp (Measured at fuel inlet connection)	°C		60	60
	°F		140	140
Prefilter / Water separator micron size	μ		10,000	
Fuel filter micron size	μ		5,000	
Governor type/make, standard	Volvo / EMS 2.2			
Injection pump type/make	Delphi E3.18			

Intake and exhaust system

		rpm	1500	1800
Air consumption at: (+25°C and 100kPa)	Standby Power	m ³ /min cfm	32 1130	42 1483
	Prime Power	m ³ /min cfm	30 1059	41 1448
Max allowable air intake restriction including piping		kPa psi	5 0,7	5 0,7
Air filter restriction clean Volvo Penta filter		kPa psi		
Heat rejection to exhaust at:	Standby Power	kW BTU/min	351 19961	432 24567
	Prime Power	kW BTU/min	317 18027	371 21098
Exhaust gas temperature after turbine at:	Standby Power	°C °F	523 973	487 909
	Prime Power	°C °F	492 918	437 819
Max allowable back pressure in exhaust line	Standby Power	kPa psi	10 1,5	10 1,5
	Prime Power	kPa psi	8 1,2	8 1,2
Exhaust gas flow at: (temp and pressure after turbine at the corresponding power setting)	Standby Power	m ³ /min cfm	82,0 2896	105,0 3708
	Prime Power	m ³ /min cfm	76,0 2684	94,0 3320

Cooling system

		rpm	1500	1800
Heat rejection radiation from engine at:	Standby Power	kW	19	23
		BTU/min	1081	1308
	Prime Power	kW	21	25
		BTU/min	1194	1422
Heat rejection to coolant at:	Standby Power	kW	200	208
		BTU/min	11374	11829
	Prime Power	kW	193	202
		BTU/min	10976	11488
Radiator cooling system type		Closed circuit		
Standard radiator core area		m ²	1,42	
		foot ²	15,28	
Fan diameter		mm	890	
		in	35,04	
Fan power consumption see diagram for actual fan ratio		kW		
		hp		
Coolant capacity,	Engine	litre	24	
		US gal	6,34	
	Engine with std radiator and hoses	litre	61	
		US gal	16,11	
	Engine with HD radiator and hoses	litre	56	
		US gal	14,79	
Coolant pump		drive/ratio	Belt / 1.85:1	
Coolant flow with standard system		l/s	6,4	7,7
		US gal/s	1,69	2,03
Minimum coolant flow		l/s	5,1	6,1
		US gal/s	1,35	1,61
Maximum outer circuit restriction, including piping		kPa	40	60
		psi	5,8	8,7
Thermostat	start to open	°C	82	
		°F	180	
	fully open	°C	92	
		°F	198	
Maximum static pressure head (expansion tank height + pressure cap setting)		kPa	100	
		psi	14,5	
Minimum static pressure head (expansion tank height + pressure cap setting)		kPa	70	
		psi	10,2	
Standard pressure cap setting		kPa	75	
		psi	10,9	
Maximum top tank temperature		°C	107	
		°F	225	
Draw down capacity. The difference between min coolant level in the expansion tank and the lowest level where the engine's coolant system still is functioning		litre	1,8	
		US gal	0,48	

VOLVO PENTA	Document No	Issue Index
	TAD1651GE	21587775

Charge air cooler system

		rpm	1500	1800
Heat rejection to charge air cooler	Standby Power	kW	107	153
		BTU/min	6085	8701
	Prime Power	kW	94	140
		BTU/min	5346	7962
Charge air mass flow	Standby Power	kg/s	0,61	0,81
	Prime Power	kg/s	0,59	0,8
Charge air inlet temp. (Charge air temp after turbo compressor)	Standby Power	°C	220	230
		°F	428	446
	Prime Power	°C	201	216
		°F	394	421
Charge air outlet temp. (Charge air temp after intercooler)	Standby Power	°C	45	45
		°F	113	113
	Prime Power	°C	43	43
		°F	109	109
Maximum pressure drop over charge air cooler incl. piping		kPa	9,5	
		psi	1,38	
Charge air pressure (After charge air cooler)		kPa	264	
		psi	38,29	
Standard charge air cooler core area		m ²	0,765	
		foot ²	8,23	

Cooling performance, STD cooling package with 890mm fan

Cooling air flow and external restriction at different radiator air temperatures based on 107°C TTT and 40% coolant. Valid at 1 atm. (radiator and cooling fan, see optional equipment)

Fan drive ratio 1:1,13

Engine speed rpm	External restriction Pa	PRIME POWER		STANDBY POWER	
		Air mass flow m ³ /s	Air on temp °C	Air mass flow m ³ /s	Air on temp. °C
1500	0	9,1	66	9,1	64
	150	8,7	65	8,7	63
	300	8,2	64	8,2	61
	450	7,6	63	7,6	60
1800	0	10,9	67	10,9	65
	150	10,5	66	10,5	64
	300	10,0	65	10,0	63
	450	9,9	63	9,9	62

Fan drive ratio 1:1,04

Engine speed rpm	External restriction Pa	PRIME POWER		STANDBY POWER	
		Air mass flow m ³ /s	Air on temp °C	Air mass flow m ³ /s	Air on temp. °C
1500	0	8,6	63	8,6	61
	150	7,9	63	7,9	60
	300	7,4	61	7,4	58
	450	6,8	60	6,8	57
1800	0	10,3	64	10,3	62
	150	9,9	63	9,9	61
	300	9,3	62	9,3	60
	450	9,0	61	9,0	59

Fan drive ratio 1:0,97

Engine speed rpm	External restriction Pa	PRIME POWER		STANDBY POWER	
		Air mass flow m ³ /s	Air on temp °C	Air mass flow m ³ /s	Air on temp. °C
1500	0	7,5	61	7,5	58
	150	7,3	61	7,3	58
	300	6,8	59	6,8	56
	450	6,4	57	6,4	54
1800	0	9,3	62	9,3	60
	150	8,9	61	8,9	59
	300	8,4	60	8,4	58
	450	8,0	59	8,0	56

Fan drive ratio 1:0,88 visco

Engine speed rpm	External restriction Pa	PRIME POWER		STANDBY POWER	
		Air mass flow m ³ /s	Air on temp °C	Air mass flow m ³ /s	Air on temp. °C
1500	0	6,6	57	6,6	54
	150	6,5	57	6,5	54
	300	6,2	55	6,2	52
	450	5,7	53	5,7	49
1800	0	8,0	58	8,0	56
	150	7,8	57	7,8	55
	300	7,4	56	7,4	53
	450	7,0	55	7,0	52

Cooling performance, HD cooling package with 890mm fan and fan drive ratio 1:0,97

Cooling air flow and external restriction at different radiator air temperatures based on 107°C TTT and 40% antifreeze (radiator and cooling fan, see optional equipment)

Engine speed rpm	External restriction Pa	PRIME POWER		STANDBY POWER	
		Air mass flow kg/s	Air on temp C°	Air mass flow kg/s	Air on temp C°
1500	0		70		68
	100		67		65
	200		65		62
	300		61		59
	400		59		55
1800	0		74		72
	100		72		70
	200		71		68
	300		70		67
	400		68		65

Engine management system

Functionality	Alternatives	Default setting
Governor mode	Isochronus / Droop	Isochronus
Governor droop	0-8 %	4,0
Governor response	Adjustable PID-constants (VODIA)	Standard
Dual speed	1500 / 1800 rpm	According to customer
Idle speed	600-1200 rpm	900 rpm
Fine speed adjustment	± 120 rpm	0,0
Stop function	Energized to Run / Stop	Energized to Stop
Preheating function	On / Off	On
Lamp test	On / Off	On

Engine sensor and switch settings

Parameter	Unit	Alarm level		Engine protection	
		Setting range	Default setting	Level	Action. Default/Alternative
Oil temp	°C	120 - 130	125	Setting +5	Shut down.
Oil pressure	Low idle	kPa	-	150,0	Shut down
	1500 rpm	kPa	-	250,0	Shut down
	1800 rpm	kPa	-	300,0	Shut down
Oil level		-	Min level	-	-
Piston cooling pressure >1000 rpm	kPa	-	150	150,0	Shut down
Coolant temp	°C	95 - 103	102	Setting +5	Shut down.
Coolant level		-	On	Low level	Shut down.
Fuel feed pressure	Low idle	kPa	-	150	-
	>1400 rpm		-	300	-
Water in fuel		-	High level	-	-
Crank case pressure	kPa	-	Increased Pressure	Increased Pressure	Shut down
Air filter pressure droop	kPa	-	5	-	-
	0,0		Alarm level		Engine protection
Altitude, above sea	m	-	-	-	Automatic derating, see section derating
Charge air temp	°C	-	80	85,0	
Charge air pressure	kPa	-	310	320,0	
Engine speed	rpm	100 - 120% of rated speed	120%	Alarm level	Shut down.

Engine protection can be disabled. For consequences please see VP International Limited Warranty Policy

Electrical system

Voltage and type		24 V / insulated from earth	
Alternator:	make/output	A	Bosch / 80
	tacho output	Hz/alt. Rev	6
	drive ratio		3.9 : 1
Starter motor	make	Melco	
	type	105 P70	
	kW	7,0	
Number of teeth on:	flywheel	153	
	starter motor	12	
Max wiring resistance main circuit		mΩ	2
Cranking current at +20°C		A	280
Crank engine speed at 20°C		rpm	150
Starter motor battery capacity:	max	Ah/A	2x225
	min at +5°C	Ah/A	-
Inlet manifold heater (at 20 V)		kW	4,0
Power relay for the manifold heater		A	1

Power take off

		rpm	1500	1800
Front end in line with crank shaft max:		Nm lbft	-	
Front end belt pulley load. Direction of load viewed from flywheel side:	max left	kW hp	-	-
	max down	kW hp	-	-
	max right	kW hp	-	-
Timing gear at compressor PTO max:		Nm lbft	600 443	
Speed ratio direction of rotation viewed from flywheel side		1,31:1/clockwise		
Timing gear at servo pump PTO max:		Nm lbft	100 74	
Speed ratio direction of rotation viewed from flywheel side		1,58:1/clockwise		
Timing gear at hydraulic pump PTO max:		Nm lbft	-	
Speed ratio direction of rotation viewed from flywheel side				
Max allowed bending moment in flywheel housing		Nm lbft	15000 11063	
Max. rear main bearing load		N lbf	5000 1124,0	







