

## CENTERLINE Low Voltage Motor Control Centers

	CENTERLINE 2100 MCC	CENTERLINE 2500 MCC
Enclosure Types Available	NEMA Types 1, 1G, 3R, 4, 12	IP20, IP42, IP54
Arc-Resistant Enclosure	Yes (IEEE C37.20.7c)	Optional
Standards	UL 845 CSA C22.2, No. 254	IEC 61439-1 IEC 60529
Section Height	90 in. (71 in. available)	2300 mm
Section Width (for Plug-in Units)	20 or 25 in.	700, 800, 900, or 1000 mm
Section Depth	15 or 20 in.	600 or 800 mm
Unit Density	Up to twelve units per vertical section	24 modules per column (one module = 80 mm)
Horizontal Bus Current Rating	600...3000 A	800...4000 A
Section Load Capacity	600 or 1200 A	600 or 1200 A
Rated Voltage	up to 600V	up to 690V
Short Circuit Withstand Ratings	42, 65, or 100 kA rms Symmetrical	50 or 80 kA for one second
<b>Units Available:</b>		
Full-Voltage Non-Reversing Starters	Yes	Yes
Full-Voltage Reversing Starters	Yes	Yes
Starters for Two-Speed Motors	Yes	Yes
Soft Starters	Yes	Yes
AC Drives	Yes	Yes
Power Monitoring Equipment	Yes	Yes
Fusible and Circuit Breaker Feeders and Mains	Yes	Yes
PLC and Controllers	Yes	Yes
Lighting Panels	Yes	Yes
Transformers	Yes	Yes
Built-in Network	Available	Available
IntelliCENTER Software	Available	Available
Preconfigured Network	Available	Available