



Image shown may not reflect actual package.

## STANDBY

**2500 ekW 3125 kVA  
60 Hz 1800 rpm 480 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- EPA Certified for Stationary Emergency Application (EPA Tier 2 emissions levels)

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### UL 2200 / CSA - Optional

- UL 2200 listed packages
  - CSA Certified
- Certain restrictions may apply.  
Consult with your Cat® Dealer.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### CAT® 3516C-HD TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

### CAT GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

### SEISMIC CERTIFICATION

- Seismic Certification available
- Anchoring details are site specific, and are dependent on many factors such as generator set size, weight, and concrete strength.  
IBC Certification requires that the anchoring system used is reviewed and approved by a Professional Engineer
- Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007
- Pre-approved by OSHPD and carries an OSP-0084-10 for use in healthcare projects in California

# STANDBY 2500 kW 3125 kVA

60 Hz 1800 rpm 480 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

| System            | Standard                                                                                                                                                                                                                                  | Optional                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Air Inlet         | <ul style="list-style-type: none"><li>• Single element canister type air cleaner</li><li>• Service indicator</li></ul>                                                                                                                    | <ul style="list-style-type: none"><li><input type="checkbox"/> Dual element &amp; heavy duty air cleaners</li><li><input type="checkbox"/> Air inlet adapters &amp; shut-off</li></ul>                                                                                                                                                                                                                                                                                                                           |
| Cooling           | <ul style="list-style-type: none"><li>• Radiator with guard</li><li>• Coolant drain line with valve</li><li>• Fan and belt guards</li><li>• Cat® Extended Life Coolant</li></ul>                                                          | <ul style="list-style-type: none"><li><input type="checkbox"/> Radiator duct flange</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Exhaust           | <ul style="list-style-type: none"><li>• Dry exhaust manifold</li><li>• Flanged faced outlets</li></ul>                                                                                                                                    | <ul style="list-style-type: none"><li><input type="checkbox"/> Mufflers and Silencers</li><li><input type="checkbox"/> Stainless steel exhaust flex fittings</li><li><input type="checkbox"/> Elbows, flanges, expanders &amp; Y adapters</li></ul>                                                                                                                                                                                                                                                              |
| Fuel              | <ul style="list-style-type: none"><li>• Secondary fuel filters</li><li>• Fuel priming pump</li><li>• Flexible fuel lines</li><li>• Fuel cooler*</li></ul>                                                                                 | <ul style="list-style-type: none"><li><input type="checkbox"/> Water separator</li><li><input type="checkbox"/> Duplex fuel filter</li></ul>                                                                                                                                                                                                                                                                                                                                                                     |
| Generator         | <ul style="list-style-type: none"><li>• Cat digital voltage regulator (CDVR) with kVAR/PF control, 3-phase sensing</li><li>• Winding temperature detectors</li><li>• Anti-condensation heaters</li></ul>                                  | <ul style="list-style-type: none"><li><input type="checkbox"/> Oversize &amp; premium generators</li><li><input type="checkbox"/> Bearing temperature detectors</li></ul>                                                                                                                                                                                                                                                                                                                                        |
| Power Termination | <ul style="list-style-type: none"><li>• Bus bar (NEMA or IEC mechanical lug holes)- right side standard</li><li>• Top and bottom cable entry</li></ul>                                                                                    | <ul style="list-style-type: none"><li><input type="checkbox"/> Circuit breakers, UL listed, 3 pole with shunt trip, 100% rated, manual or electrically operated</li><li><input type="checkbox"/> Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip, manual or electrically operated</li><li><input type="checkbox"/> Bottom cable entry</li><li><input type="checkbox"/> Power terminations can be located on the right, left and/or rear as an option.</li></ul>                                     |
| Governor          | <ul style="list-style-type: none"><li>• ADEM™ 3</li></ul>                                                                                                                                                                                 | <ul style="list-style-type: none"><li><input type="checkbox"/> Load share module</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Control Panels    | <ul style="list-style-type: none"><li>• EMCP 4.2 Genset controller</li></ul>                                                                                                                                                              | <ul style="list-style-type: none"><li><input type="checkbox"/> Digital I/O Module</li><li><input type="checkbox"/> Generator temperature monitoring &amp; protection</li></ul>                                                                                                                                                                                                                                                                                                                                   |
| Lube              | <ul style="list-style-type: none"><li>• Lubricating oil and filter</li><li>• Oil drain line with valves</li><li>• Fumes disposal</li><li>• Gear type lube oil pump</li></ul>                                                              | <ul style="list-style-type: none"><li><input type="checkbox"/> Oil level regulator</li><li><input type="checkbox"/> Deep sump oil pan</li><li><input type="checkbox"/> Electric &amp; air prelube pumps</li><li><input type="checkbox"/> Manual prelube with sump pump</li><li><input type="checkbox"/> Duplex oil filter</li></ul>                                                                                                                                                                              |
| Mounting          | <ul style="list-style-type: none"><li>• Rails - engine / generator / radiator mounting</li><li>• Rubber anti-vibration mounts (shipped loose)</li></ul>                                                                                   | <ul style="list-style-type: none"><li><input type="checkbox"/> Spring-type vibration isolator</li><li><input type="checkbox"/> IBC Isolators</li></ul>                                                                                                                                                                                                                                                                                                                                                           |
| Starting/Charging | <ul style="list-style-type: none"><li>• 24 volt starting motor(s)</li><li>• Batteries with rack and cables</li><li>• Battery disconnect switch</li></ul>                                                                                  | <ul style="list-style-type: none"><li><input type="checkbox"/> Battery chargers</li><li><input type="checkbox"/> Charging alternator</li><li><input type="checkbox"/> Oversize batteries</li><li><input type="checkbox"/> Ether starting aid</li><li><input type="checkbox"/> Heavy duty starting motors</li><li><input type="checkbox"/> Barring device (manual)</li><li><input type="checkbox"/> Air starting motor with control &amp; silencer</li><li><input type="checkbox"/> Jacket water heater</li></ul> |
| General           | <ul style="list-style-type: none"><li>• Right-hand service</li><li>• Paint - Caterpillar Yellow except rails and radiators are gloss black</li><li>• SAE standard rotation</li><li>• Flywheel and flywheel housing - SAE No. 00</li></ul> | <ul style="list-style-type: none"><li><input type="checkbox"/> UL 2200</li><li><input type="checkbox"/> CSA certification</li><li><input type="checkbox"/> CE Certificate of Conformance</li><li><input type="checkbox"/> Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007</li></ul>                                                                                                                                                                        |
| Note              | Standard and optional equipment may vary for UL 2200 Listed Packages. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics.                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

# STANDBY 2500 kW 3125 kVA

60 Hz 1800 rpm 480 Volts



## SPECIFICATIONS

### CAT GENERATOR

Cat Generator

Frame size..... 1842

Excitation..... Permanent Magnet

Pitch..... 0.6667

Number of poles..... 4

Number of bearings..... 2

Number of Leads..... 006

Insulation..... UL 1446 Recognized Class H with  
tropicalization and antiabrasion  
- Consult your Caterpillar dealer for available voltages

IP Rating..... IP23

Alignment..... Closed Coupled

Overspeed capability..... 125

Wave form Deviation (Line to Line)..... 003.00

Voltage regulator..... 3 Phase sensing with selectable  
volts/Hz

Voltage regulation..... Less than +/- 1/2% (steady state)

Less than +/- 1/2% (w/3% speed change)

### CAT DIESEL ENGINE

3516C-HD ATAAC, V-16, 4-Stroke Water-cooled Diesel

Bore..... 170.00 mm (6.69 in)

Stroke..... 215.00 mm (8.46 in)

Displacement..... 78.08 L (4764.73 in<sup>3</sup>)

Compression Ratio..... 14.7:1

Aspiration..... TA

Fuel System..... Electronic unit injection

Governor Type..... ADEM3

### CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- kW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVar) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

# STANDBY 2500 kW 3125 kVA

60 Hz 1800 rpm 480 Volts



## TECHNICAL DATA

| Open Generator Set - - 1800 rpm/60 Hz/480 Volts                                                                                                                                                                                        | DM8266                                                                |                                                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------|
| EPA Certified for Stationary Emergency Application<br>(EPA Tier 2 emissions levels)                                                                                                                                                    |                                                                       |                                                                                    |
| <b>Generator Set Package Performance</b><br>Genset Power rating @ 0.8 pf<br>Genset Power rating with fan                                                                                                                               | 3125 kVA<br>2500 kW                                                   |                                                                                    |
| <b>Fuel Consumption</b><br>100% load with fan<br>75% load with fan<br>50% load with fan                                                                                                                                                | 656.8 L/hr<br>510.8 L/hr<br>372.4 L/hr                                | 173.5 Gal/hr<br>134.9 Gal/hr<br>98.4 Gal/hr                                        |
| <b>Cooling System<sup>1</sup></b><br>Air flow restriction (system)<br>Air flow (max @ rated speed for radiator arrangement)<br>Engine Coolant capacity with radiator/exp. tank<br>Engine coolant capacity<br>Radiator coolant capacity | 0.12 kPa<br>2800 m <sup>3</sup> /min<br>504.0 L<br>233.0 L<br>271.0 L | 0.48 in. water<br>98881 cfm<br>133.1 gal<br>61.6 gal<br>71.6 gal                   |
| <b>Inlet Air</b><br>Combustion air inlet flow rate                                                                                                                                                                                     | 204.2 m <sup>3</sup> /min                                             | 7211.3 cfm                                                                         |
| <b>Exhaust System</b><br>Exhaust stack gas temperature<br>Exhaust gas flow rate<br>Exhaust flange size (internal diameter)<br>Exhaust system backpressure (maximum allowable)                                                          | 490.7 °C<br>554.5 m <sup>3</sup> /min<br>203.2 mm<br>6.7 kPa          | 915.3 °F<br>19582.0 cfm<br>8.0 in<br>26.9 in. water                                |
| <b>Heat Rejection</b><br>Heat rejection to coolant (total)<br>Heat rejection to exhaust (total)<br>Heat rejection to aftercooler<br>Heat rejection to atmosphere from engine<br>Heat rejection to atmosphere from generator            | 826 kW<br>2502 kW<br>786 kW<br>161 kW<br>101.5 kW                     | 46975 Btu/min<br>142288 Btu/min<br>44700 Btu/min<br>9156 Btu/min<br>5772.3 Btu/min |
| <b>Alternator<sup>2</sup></b><br>Motor starting capability @ 30% voltage dip<br>Frame<br>Temperature Rise                                                                                                                              | 6559 skVA<br>1842<br>150 °C                                           | 270 °F                                                                             |
| <b>Lube System</b><br>Sump refill with filter                                                                                                                                                                                          | 466.0 L                                                               | 123.1 gal                                                                          |
| <b>Emissions (Nominal)<sup>3</sup></b><br>NOx g/hp-hr<br>CO g/hp-hr<br>HC g/hp-hr<br>PM g/hp-hr                                                                                                                                        | 5.32 g/hp-hr<br>.42 g/hp-hr<br>.1 g/hp-hr<br>.037 g/hp-hr             |                                                                                    |

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>2</sup> Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# STANDBY 2500 kW 3125 kVA

60 Hz 1800 rpm 480 Volts



## RATING DEFINITIONS AND CONDITIONS

---

**Meets or Exceeds International Specifications:** AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

# STANDBY 2500 ekW 3125 kVA

60 Hz 1800 rpm 480 Volts



## DIMENSIONS

---

| Package Dimensions |           |           |
|--------------------|-----------|-----------|
| Length             | 6982.5 mm | 274.9 in  |
| Width              | 2569.2 mm | 101.15 in |
| Height             | 3009.3 mm | 118.48 in |

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #3292332).

Performance No.: DM8266

Feature Code: 516DE6N

Gen. Arr. Number: 2523944

Source: U.S. Sourced

November 06 2012

20932144

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

2012 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.