

Control

STARTS 764 <<
HOURS 01413.7

Reset

Menu

Panel Lights

Self Test



1-877-POWER-NOW



POWER
RENT

05 2896





750-4023

1-877-POWE-NOV

Powel Trail

Cummins

Cummins

1877-2CWR-NOW

750-4023



POWER
UNIT





Cutler-Hammer SPB 100

3000 AMP FRAME
3 POLE
FOR AC 50/60 HZ ONLY

Refer To Left Side
For Accessory Info.

MAXIMUM RMS SYMMETRICAL AMPS

VOLTS INTERRUPTING	SHORT TIME	
240	100,000	35,000
480	100,000	35,000
600	85,000	35,000

SUITABLE FOR CONTINUOUS OPERATION AT
100 PERCENT OF RATING PLUG IF USED IN AN
ENCLOSURE (H0000 INCHES) 42 X 18 X 17
VENTILATION REQUIRED IN SQUARE INCHES
76 IN FRONT AND 175 IN BACK

RATING PLUGS-CONTINUOUS AMPERE RATINGS
FOR DIGITRIP RMS 210, 510, 610, 810, 910
OPTIM 750 AND 1050 USE RPSS300****

1600, 2000, 2500, 3000 *INSERT FIRST THREE
DIGITS OF AMPS TO
COMPLETE

INTERRUPTING CAPACITY
RMS SYMMETRICAL AMPS
IEC 947-2 (66) 480 V 50/60 Hz

U _{sc}	I _{cu}	I _{cs}	I _{cm}
250-240	100	50	100
300-415	100	50	100
550-220	50	25	50

U_{imp} 5kV
U_i = 1000VAC

CATEGORY B

PO 364012779
BYRGO HPMP650225-49

B782C3200173420629720000001023

SPBR330F

B 74E9190.03 20 AUG 99



Cutler-Hammer

Digital
RMS 5

Catalog Number

0566510 (D)



Long Delay
Setting

Long Delay

Digital RMS Rating Plug
For Use in SPB Breakers Only

Cat. SP630A150

Stored Energy

Charged

Contact Position



Push to Close



