

WOODWARD

PROACT 75 ACTUATOR

PART NO. 4-100-0050

SERIAL NO. _____

MODEL NO. _____

CUSTOMER NO. _____

WOODWARD GOVERNOR COMPANY - FORT COLLINS, CO

MAGNAMAX DVR

CE

SYNCHRONOUS AC GENERATOR

MODEL 744RSL4054
 SERIAL WA-573742-0710
 FRAME 744 RPM 1800
 PH 3 HZ 60 TYPE RSL
 ENCL. OPEN PF 0.8 AMB. 27 °C
 INS. CLASS H1 RISE BY RES. 130 °C
 FIELD AMPS 2.2 FIELD VOLTS 55



CONTINUOUS

KW VOLTS
 KVA AMPS

STANDBY SERVICE

KW 2000 VOLTS 277/480Y
 KVA 2500 AMPS 3007

BEARING BEARING A-7812R-110
 REGULATOR NO. DVR2000E RPM 180 R_F 300
 72555

GREASING INSTRUCTIONS

LUBRICATE GENERATOR EVERY 3000 OPERATING HOURS OR ANNUALLY WITH 4.2 CUBIC INCHES OF MARATHON POLYREX EM OR EQUIVALENT GREASE WITH A TEMPERATURE RANGE OF -30 °C TO 175 °C



WAUSAU, WISCONSIN 54401



MODEL D2000FRY4
 SERIAL 322128-1-1-0710
 RATING STANDBY
 ENGINE Mitsubishi S10R-Y1PTAA2-1
 RPM 1800 Hz 60
 KW 2000 KVA 2500

VOLTS	AMPS	PHASE	WIRE	PF
277/480	3007	3	A/A	0.8

WIRE CONFIG: Ww

GENERATOR RISE (°C) 130
 AMPS/TERM 3007
 INS. CLASS: R

www.rtu-online.com



NOTICE

When working, the following must be done to avoid damage to the electronic controls or the engine:

- Both the positive (+) and the negative (-) battery leads must be disconnected before welding.
- Ground cables must be 25' close proximity to welding location.
- engine must never be used as a grounding point.
- Working on the engine or engine mounted components is NEVER recommended.
- Disconnect the connectors from the Engine Control Unit.

CSA Certified

FOR ELECTRICAL EQUIPMENT ONLY
 POUR MATÉRIEL
 ÉLECTRIQUE SEULEMENT

CAUTION

CAUTION: FOR STANDBY SERVICE CONNECT SWITCH OR GENERATOR TO SUITABLE RATED TRIPPER SWITCH IN ACCORDANCE WITH CANADIAN ELECTRICAL CODE, PART 1.
 ATTENTION: POUR L'ALIMENTATION EN SERVICE, CONNECTER LE SWITCHE DE LA GÉNÉRATEUR À UN COMBUSTEUR DE CALIBRE APPROPRIÉ, CONFORMÉMENT AU CODE CANADIEN DE L'ÉLECTRICITÉ, NORMES PARTIE-1.

CAUTION

FOR USE IN A WEATHER PROTECTED AREA ONLY
 EMPLOYER UNIQUEMENT DANS UN EMPLACEMENT À L'ABRI DES INTÉMPÉRIES



Serial No.

MFG Date

XXXXXXXXXX



XX. 200X

Model

S16R-Y1PTAA2-1

Rated Output 2882HP / 1800RPM

2150kW / 1800min

MITSUBISHI
HEAVY INDUSTRIES, LTD.

SAGAMIHARA, JAPAN

0763-22000

PROACT PLUS

DIGITAL SPEED CONTROL 4-20 mA FUEL LIMITER

WOODWARD



CAUTION

ASSEMBLY CONTAINS PARTS SUBJECT TO DAMAGE BY ELECTROSTATIC DISCHARGE (ESD). PRECAUTIONS SHOULD BE OBSERVED TO PREVENT ESD FROM DAMAGING INTERNAL PARTS.

